

FIBER OPTIC COMPONENTS

Features **E-2000 CONNECTOR**

- * E-2000 Simplex or Duplex
- * ANSI 、 IEC 、 TIA/EIA 、 NTT and JIS standard compatible
- * UL-rated plastic housing and boot in a variety of colors with 0.9mm, 2.0mm or 3.0mm
- * Precision mechanical dimensions
- * Zirconia ferrule PC or 8 degree APC diameter 125~128 um high concentricity
- * Single mode, Multimode and Angle PC
- * Multi-piece type or one-piece type is available
- * All parts compliant with ROHS

Application

- Telecommunication
- CATV
- LAN & WAN
- Network
- Broadband
- FTTH



Parameter

Item	Parameter		
	Single-Mode	Multi-Mode	APC
Insertion Loss	Type 0.2-0.4dB, Max 0.5-1dB		
Durability (1000 Mating)	0.2dB Max.		
Operating Temperature	-40°C~+75°C		
Storage Temperature	-40°C~+85°C		
Remark:	Ferrule inner diameter tolerance +1/-0um Ferrule outer diameter tolerance +/-0.5 um		

Ordering Information

CODE	FERRULE	TYPE	HOUSING	B
1	Single Mode	1 Simplex	1 0.9	1 Blue
2	Multimode	2 Duplex	2 2.0	2 Green
3	Angle PC		3 3.0	