


CHASSIS SUPPORT 16 PORT



Description

- >The power of the Rack can be supplied by the type of single power or dual power. Adopting dual power supply, the load of each power can be reduced and
- >The life of the power would extend. When one power supply is at fault, the other one can still work independently. It would enhance the reliability of the RACK
- > Supplying the Converters or Powers to be plugged and played
- > It is possessed of stable performance, large capacity of power supply, and ease for management and maintenance.
- > 2U high: 19-inch standard design

TECHNICAL SPECIFICATIONS:

- >Capacity:16 slots available
- >Power: Input: AC 100 ~ 260V,50 ~60 HZ; or DC48V
- >Output : DC+5V,12A(Single Power)or24A(Dual Power)
- >Vein : <=50mv
- >Noise : <=50mv
- >Power protection : protection from over voltage, over current and short circuit
- >Working temperature : 0~50C°
- >Storage temperature : -20~+70C°
- >Relative Humidity:5%~95%
- >Dimensions : 485(width)×245(length)×90mm(high)mm

► DISTRIBUTED BY

THAISOFTECH INTERGROUP CO.,LTD.

131 Srinakarin Park Village 1 , Nongbon Pravate, Bangkok 10250
Tel : (+66) 2-716-3565 , Fax : (+66) 2-716-3566