





## Coax Cable

Photo	Model No.	Conductor		Dielectric		Shield		Outer Jacket
		Material	Dia.	Material	Dia.	Material	Coverage	
 	RG59 23AWG	BC	1/0.58	S-PE	3.70	BC/CCA	80%	6.0
	Mini RG59	BC	1/0.48	S-PE	3.00	BC/CCA	80%	5.0
	3C-2V	BC	1/0.50	S-PE	3.10	BC/CCA	80%	5.40
	5C-2V	BC	1/0.80	S-PE	4.90	BC/CCA	80%	7.20
	SYV75-2-2	BC	1/0.25	S-PE	1.50	BC	85%	2.90
	RG58	BC	1/0.80	S-PE	3.00	BC/CCA	80%	5.00
	RG213	BC	7/0.75	S-PE	7.25	BC/CCA	80%	10.30
	RG214	BC	7/0.75	S-PE	7.25	BC/CCA	60%+80%	10.80
 	RG59 20AWG	BC	1/0.80	F-PE	3.70	TC/AL	100%+80%	6.0
	RG6	BC/CCS	1/1.0	F-PE	4.60	TC/AL	100%+43%	7.0
	HD-SDI Cable (RG59)	BC	1/0.81	F-PE	3.66	TC/AL	100%+90%	6.0
	HD-SDI Cable (RG-6)	BC	1/1.02	F-PE	4.60	TC/AL	100%+90%	7.0
	RG11	BC/CCS	1/1.66	F-PE	7.25	TC/AL	100%+40%	10.3