


Security & Alarm Cable

Photo	Model No.	Conductor		Insulation	Shield	Outer Jacket	Max. Conductor Resistance@ 20°C	Mini. Insulation Resistance@ 70°C (M/KM)
		Material	Dia.					
	SA-4*0.12	BC/TC	4x7/0.15	1.10	/	3.70	158	0.016
	SA-6*0.12	BC/TC	6x7/0.15	1.10	/	4.30		
	SA-8*0.12	BC/TC	8x7/0.15	1.10	/	4.90		
	SA-10*0.12	BC/TC	10x7/0.15	1.10	/	5.60		
	SA-4*0.22	BC/TC	4x7/0.20	1.20	/	3.90	92.3	0.014
	SA-6*0.22	BC/TC	6x7/0.20	1.20	/	4.60		
	SA-8*0.22	BC/TC	8x7/0.20	1.20	/	5.20		
	SA-10*0.22	BC/TC	10x7/0.20	1.20	/	6.00		
	SA-4*0.12S	BC/TC	4x7/0.15	1.10	Al-foil	3.80	158	0.016
	SA-6*0.12S	BC/TC	6x7/0.15	1.10	Al-foil	4.40		
	SA-8*0.12S	BC/TC	8x7/0.15	1.10	Al-foil	5.00		
	SA-10*0.12S	BC/TC	10x7/0.15	1.10	Al-foil	5.70		
	SA-4*0.22S	BC/TC	4x7/0.20	1.20	Al-foil	4.00	92.3	0.014
	SA-6*0.22S	BC/TC	6x7/0.20	1.20	Al-foil	4.80		
	SA-8*0.22S	BC/TC	8x7/0.20	1.20	Al-foil	5.40		
	SA-10*0.22S	BC/TC	10x7/0.20	1.20	Al-foil	6.10		